

AGMA/EP

Industrial Extreme Pressure Gear and Rock Drill Oil

General Description

The AGMA/EP Gear Oil series of lubricants are special formula gear lubricants for heavy duty industrial gear sets as specified by the AGMA (American Gear Manufacturers Association).

AGMA/EP Gear Oils are formulated with premium high quality base oils to provide optimum load carrying capability, water separation and oxidation resistance. The additive system incorporated in this series of oils provides extreme pressure (EP) and antiwear protection, superior oxidative and thermal stability, increased protection against rust and corrosion and excellent seal compatibility.

At the high localized temperatures achieved under heavy load conditions, the sulfur-phosphorus EP additive in AGMA/EP Gear Oils chemically reacts with the metal surfaces in order to prevent the welding, scoring and galling that may occur as the oil film is broken. By modifying the metal surfaces at contact in this manner, wear is reduced and gear life is extended.

AGMA Gear Oils are not to be used in automotive differential gear sets that require the use of API GL-5 rated gear oils, and are not food grade products.

Several viscosity grades, as described in the typical properties section, have tackifier added to provide added adhesion for rock drill and pneumatic tool performance.

Features and Benefits

E.P. Performance: Excellent extreme pressure properties reduce wear and maintenance costs where applicable.

Long Oil Life: Enhanced oxidative and thermal stability lead to longer fluid life.

Rust and Corrosion Protection: Superior rust and corrosion prevention leads to prolonged equipment life.

Seal Compatibility: Excellent seal compatibility decreases degradation and swelling of seal materials.

Typical Application

Industrial gear sets calling for a premium industrial gear oil, a gear oil with AGMA 250.04 or U.S. Steel 224 performance, as well as enclosed gear drives including spur, helical, double helical or "herringbone" and straight bevel types.

Worm gear sets that are comprised entirely of steel, or ferrous, components typically accept an AGMA style of gear oil readily. Worm gear sets that contain copper, brass, bronze, or other red and yellow metal alloys generally should not use an AGMA style of gear lubricant.

This product is suitable for splash, chain or ring oil delivery as well as for circulation, or pump delivery.

AGMA/EP

Industrial Extreme Pressure Gear and Rock Drill Oil

Typical Customer

Owners and operators of:

- Enclosed gear sets, such as industrial plants
- Rock drill equipment
- Pneumatic tools

Health & Safety

A complete material safety data sheet is available upon request. Used oil contains by-products which may be harmful. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute - return used oil to a collection center.

Typical Properties

AGMA Grade	2EP	3EP	4EP	5EP	6EP	7EP
Rock Drill Grade		Medium	Med/Hvy	Heavy	Ex.Hvy	
ISO VG	68	100	150	220	320	460
API Gravity	30.7	30.7	27.0	26.8	27.1	24.5
Viscosity @ 100C, cSt	8.43	11.0	14.6	19.3	23.9	30.5
Viscosity @ 40C, cSt	66.3	99	149	228	316	458
Viscosity Index		96	96	96	96	96 96
Flash Point, F	420	425	430	435	435	440
Pour Point, F	-15	-11	-6	-6	0	+5

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.