

# Auto Gold™ Multi-Vehicle ATF

## Synthetic Blend Automatic Transmission Fluid

### General Description

**Auto Gold™ Multi-Vehicle ATF** contains an advanced additive system along with specially selected mineral and synthetic base oils that provide service fill performance in a wide variety of automatic transmissions. It gives protection that meets or exceeds the industry's highest quality standards.

It includes most GM, Ford, Chrysler, Jeep, Saturn, Honda/Acura, Toyota, Nissan, Mitsubishi, Hyundai, Mercedes, BMW, VW/Audi and other transmissions. **Always check the owner's manual for details.**

**Auto Gold™ Multi-Vehicle ATF** is a balanced field tested formulation that gives assurance of the best possible wear protection on gears and transmission parts for a longer life. Excellent friction and anti-shudder durability for smooth and consistent shifting. Improved low temperature operability, resistance to high temperature oxidation and thermal degradation along with corrosion and foam inhibitors for year around protection. In addition, good compatibility with seal material minimizes leaks. It contains a shear-stable polymer that minimizes oil viscosity change over a wide temperature range. All these performance features provide enhanced transmission performance and life.

### Features and Benefits

**Multi-Vehicle Capability:** Formulated to meet the stringent wear, friction, and operational requirements of most automatic transmissions for a smooth driving experience.

**Wear Protection:** The highest level of wear protection for gears and internal moving parts allowing for maximum transmission life.

**Friction Retention:** Uniquely balanced frictional properties provide anti-shudder durability, smooth shifting and precise lock-up throughout the service interval.

**High Temperature Protection:** Excellent oxidation and thermal protection that reduces sludge, varnish, and deposits for longer life.

**Cold Temperature Operability:** Improved cold temperature flow characteristics assures ease of pumping, quick start up and smooth shifting, even at extremely low temperatures.

#### Typical Application:

Suitable for use in applications where manufacturers recommend:

- Dex VI,III,II, Type A, Suffix A
- Mer V,SP,LV,138CJ,166H
- Chy +4,+3
- Asian and European Cars
- JASO 1A
- ZF
- Voith
- Allison C-4/C-3

**Not suitable for use in CVT (continuously variable transmissions), Ford Type F, and Allison TES-295**

# Auto Gold™ Multi-Vehicle ATF

## Synthetic Blend Automatic Transmission Fluid

### Typical Customer:

Owners and operators of:

- Most GM, Chrysler, Ford, European, and Asian brands of automobiles and light trucks.
- Quick Lubes.
- Automobiles/Trucks/Buses calling for ATF fluids in automatic transmissions.
- Power Steering units calling for Mer/Dex ATF fluids.
- Hydraulic systems calling for ATF fluids.

### Health & Safety:

A complete material safety data sheet is available upon request. Used oil may be harmful, avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute - return used oil to a collection center.

### Auto Gold Multi-Vehicle ATF Typical Properties

Viscosity, cSt @ 40°C	32.9
@ 100°C	7.2
Viscosity Index	195
Brookfield @ -40 cP	9000
API Gravity / Lbs gal	33.1 / 7.16
Pour Point, °F / °C	-58 / -51
Flash Point, °F / °C	385 / 196
Color	RED

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.